


ARMTO Light Weight Oil Applications




- 1" NPT Steel Screw Plug
- Steel Sheath Element
- 20 W/In²
- 0.25 - 1.5 kW
- Integral Thermostat (SPST)
- 120 and 240 Volt, Single Phase
- General Purpose or Moisture Resistant/Explosion Resistant Terminal Enclosure



E1 — Dimensions (Inches)



E2 — Dimensions (Inches)



Specifications and Ordering Information

							T4 — Temperature (60 - 187°F)			T5 — Temperature (60 - 240°F)			T8 — Temperature (0 - 127°F)		
kW	Volts	Phase	W/In ²	No. Elem.	DIM B (In.)	Wt. (Lbs.)	Model	Stock	PCN	Model	Stock	PCN	Model	Stock	PCN
E1 General Purpose¹															
0.25	120	1	20	1	6-1/2	2	ARMTO-250T4	S	292883	ARMTO-250T5	NS	319003	ARMTO-250T8	NS	319011
0.375	120	1	20	1	9-1/2	3	ARMTO-375T4	S	292891	ARMTO-375T5	NS	319046	ARMTO-375T8	NS	319054
0.375	240	1	20	1	9-1/2	3	ARMTO-375T4	NS	292912	ARMTO-375T5	NS	319089	ARMTO-375T8	NS	319097
0.5	120	1	20	1	12-1/2	3	ARMTO-500T4	S	292904	ARMTO-500T5	NS	319126	ARMTO-500T8	S	319134
0.5	240	1	20	1	12-1/2	3	ARMTO-500T4	NS	292980	ARMTO-500T5	NS	319169	ARMTO-500T8	S	319177
1	120	1	20	1	25	3	ARMTO-1000T4	NS	038703	ARMTO-1000T5	NS	038746	ARMTO-1000T8	NS	038789
1	240	1	20	1	25	3	ARMTO-1000T4	NS	038711	ARMTO-1000T5	NS	038754	ARMTO-1000T8	NS	038797
1.5	120	1	20	1	38	4	ARMTO-1500T4	NS	038720	ARMTO-1500T5	NS	038762	ARMTO-1500T8	NS	038800
1.5	240	1	20	1	38	4	ARMTO-1500T4	NS	038738	ARMTO-1500T5	NS	038770	ARMTO-1500T8	NS	038818
E2 Moisture Resistant/Explosion Resistant²															
0.25	120	1	20	1	6-1/2	5	ARMTO-250E2T4	S	292963	ARMTO-250E2T5	NS	319020	ARMTO-250E2T8	NS	319038
0.375	120	1	20	1	9-1/2	5	ARMTO-375E2T4	NS	292939	ARMTO-375E2T5	NS	319062	ARMTO-375E2T8	NS	319070
0.375	240	1	20	1	9-1/2	5	ARMTO-375E2T4	NS	292920	ARMTO-375E2T5	NS	319100	ARMTO-375E2T8	NS	319118
0.5	120	1	20	1	12-1/2	5	ARMTO-500E2T4	S	292971	ARMTO-500E2T5	NS	319142	ARMTO-500E2T8	NS	319150
0.5	240	1	20	1	12-1/2	5	ARMTO-500E2T4	NS	292998	ARMTO-500E2T5	NS	319185	ARMTO-500E2T8	NS	319193
1	120	1	20	1	25	6	ARMTO-1000E2T4	NS	038826	ARMTO-1000E2T5	NS	038869	ARMTO-1000E2T8	NS	038906
1	240	1	20	1	25	6	ARMTO-1000E2T4	NS	038834	ARMTO-1000E2T5	NS	038877	ARMTO-1000E2T8	NS	038914
1.5	120	1	20	1	38	7	ARMTO-1500E2T4	NS	038842	ARMTO-1500E2T5	NS	038885	ARMTO-1500E2T8	NS	038922
1.5	240	1	20	1	38	7	ARMTO-1500E2T4	NS	038850	ARMTO-1500E2T5	NS	038893	ARMTO-1500E2T8	NS	038930

Stock Status: S = stock NS = non-stock
To Order—Specify model, volts, phase, kW, PCN and quantity.

1. Heaters with General Purpose Enclosures are UL Listed and CSA Certified.
2. Heaters with Moisture Resistant/Explosion Resistant Enclosures are ^CCSA_{US}® Certified.



Same-day shipping on stock item orders received before 4 pm CST.
 3-day shipping on assembly-stock items.