



APS-4C Snow Melting/De-Icing Controller

- Snow Melting/De-Icing Controller
- Satellite Contactor Interface for Larger Systems
- Energy Management Computer (EMC) Interface
- Accommodates MI, Constant Wattage and Self-Regulating Heaters
- Multiple Sensor Capability
- Advanced Ground Fault Protection
- Heater Hold-On And Test Capabilities
- C-UL-US Listed
- Simple to Install and Operate
- Low System Costs
- Minimum Energy Costs
- 30mA Grount Fault Protection



Description

The APS-4C Snow Switch when used with one, or more, compatible sensors automatically controls snow/ice melting heaters for minimum energy costs. Applications include pavement, sidewalk, loading dock, roof, gutter and down spout snow/ice melting in commercial and industrial environments. The APS-4C is interchangeable with the earlier APS-4.

The adjustable hold-on timer continues heater operation for up to 10 hours after snow stops to ensure complete melting. The optional RCU-4 Remote Control Unit can be located where system operation can be conveniently observed. It duplicates many of the APS-4C front panel functions.

The APS-4C provides advanced patented and patent pending ground fault equipment protection (GFEP) as required by the USA and Canadian National Electric Codes. The GFEP automatically tests itself every time the heater contactors operate and once every 24 hours. The trip current can be set at 60 or 120 mA via an internal switch or retained at the 30 ma default value. As an aid to troubleshooting heater ground faults, the APS-4C provides an output that can indicate the ground current on a service person's portable DVM.

The calibrated 40°F to 90°F (4°C to 32°C) high limit thermostat prevents excessive temperatures when using constant wattage and MI heaters. It also permits safe testing at outdoor temperatures too high for continuous heater operation. The temperature sensor is included.

The APS-4C provides a complete interface for use in environments supervised by an energy management computer (EMC). This feature can also be used for general purpose remote control and annunciation.

All sensor and communications wiring is NEC Class 2. This simplifies installation while enhancing fire and shock safety. The APS-4C can interface up to six sensors from the CIT-1 product family. Using more sensors provides superior performance by better matching the controller to site performance requirements.

The APS-4C is an exceptionally capable deicing controller. For complete information describing its application, installation and features, please contact your local Chromalox Sales Office.

The ETI logo is a registered trademark of Environmental Technology, Inc. SIT is a trademark of Environmental Technology, Inc. Copyright 2000, All rights reserved.

APS-4C Snow Melting/De-icing Controller

(cont'd.)

Specifications

| | | |
|---|------------|--|
| General | | |
| Area of use | | Nonhazardous locations |
| <hr/> | | |
| Enclosure | | |
| Protection | | NEMA 3R |
| Cover attachment | | Hinged polycarbonate cover, lockable |
| Entries | | 1 × 1-1/16" entry (top) for NEC Class 2 connections 2 × 1-11/16" entries (bottom) for supply and load power, except 277 VAC single phase 2 × 1-1/16" entries (bottom) for supply and load power, 277 VAC single phase only |
| Material | | Polycarbonate |
| Mounting | | Wall mount |
| Dimensions | | 5-1/2" (L) × 8-1/8" (W) × 4-3/8" (H) 140mm (L) × 207mm (W) × 112mm (H) |
| <hr/> | | |
| Control | | |
| Supply Voltage | PCN 389853 | 208-240 VAC, 35 VA, three phase 50/60 Hz |
| | PCN 389895 | 277 VAC, 45 VA, single phase 50/60 Hz |
| | PCN 389861 | 277/480 VAC, 45 VA, three phase 50/60 Hz |
| | PCN 399525 | 600 VAC, 50 VA, three phase 50/60 Hz |
| Load | PCN 389855 | 208-240 VAC, 50 amp max. resistive |
| | PCN 389845 | 277 VAC, 40 amp max. resistive |
| | PCN 389861 | 277/480 VAC, 50 amp max. resistive |
| | PCN 399525 | 600 VAC, 50 amp max. resistive |
| Contact Type | | 3 Form A (NO) |
| Weight | | 3 Pounds (not including sensors) |
| Maximum Ratings | | Voltage: 600 VAC Current: 50 Amps |
| Heater Hold-On timer | | 0 - 10 hours; actuated by snow stopping or toggle switch |
| System Test | | Switch toggles heater contact on and off. If temperature exceeds high limit, heater cycles prevent damage. |
| <hr/> | | |
| Ground Fault Equipment Protection (GFEP) | | |
| Set point | | 30 mA (default); 60 mA & 120 mA selectable by DIP switch |
| Automatic self-test | | Mode A: Verifies GFEP function before contactors operate Mode B: Verifies GFEP and heaters every 24 hours |
| Manual test/reset | | Toggle switch provided for this function |
| Maintenance facility | | DC output proportional to ground current provided for troubleshooting the heater system |
| <hr/> | | |
| Snow/Ice Sensors | | |
| Maximum Quantity | | Up to 6 sensors from the CIT-1 product family |
| Circuit Type | | NEC Class 2 |
| Lead Length | | Up to 500' (152m) using 18 AWG 3-wire jacketed cable Up to 2,000' (609m) using 12 AWG 3-wire jacketed cable |
| <hr/> | | |
| High Limit Thermostat | | |
| Adjustment range | | 40°F to 90°F (4°C to 32°C) |
| Dead band | | 1°F (0.6°C) |
| Circuit type | | Thermistor network |
| Sensor interface | | NEC Class 2 |
| Lead length | | Up to 500' (152m) using 18 AWG 2-wire jacketed cable Up to 1,000' (304m) using 12 AWG 2-wire jacketed cable |

APS-4C Snow Melting/De-icing Controller (cont'd.)


Energy Management Computer (EMC) Interface

| | |
|---------|---|
| Inputs | OVERRIDE ON (10 mA dry switch contact) OVERRIDE OFF (10 mA dry switch contact) |
| Outputs | SUPPLY (10 mA dry switch contact) SNOW (10 mA dry switch contact) HEAT (10 mA dry switch contact) HIGH TEMP (10 mA dry switch contact) ALARM (10 mA dry switch contact) |

Environmental

| | |
|-----------------------|--------------------------------|
| Operating temperature | -40°F to 160°F (-40°C to 71°C) |
| Storage temperature | -50°F to 180°F (-45°C to 82°C) |

Dimensions



Specifications and Ordering Information

| Model Number | PCN | Stock |
|--|---------------|----------|
| APS-4C Control Panel (277 Volt Single Phase) | 389845 | S |
| APS-4C Control Panel (208-240 Volt 3-Phase) | 389853 | S |
| APS-4C Control Panel (277/480 Volt 3-Phase) | 389861 | S |
| APS-4C Control Panel (600 Volt 3-Phase) | 399525 | NS |

Stock Status: S = stock AS = assembly stock NS = non-stock
To Order—Specify model, PCN and quantity.