


Immersion


ARMTO-2 Medium Weight Oil Applications

- 2" NPT Steel Screw Plug
- Steel Sheath Elements
- 15 W/in²
- 2 - 6 kW
- Integral Thermostat (DPST)
- 240 and 480 Volt, Single Phase
- General Purpose or Moisture Resistant/Explosion Resistant Terminal Enclosure

E1 — Dimensions (Inches)



E2 — Dimensions (Inches)



SCREW PLUG



Same-day shipping on stock item orders received before 4 pm CST. 3-day shipping on assembly-stock items.

Specifications and Ordering Information

								T3 — Temperature (200 - 550°F)			T2 — Temperature (60 - 250°F)			T1 — Temperature (0 - 100°F)		
kW	Volts	Phase	W/in ²	No. Elem.	DIM B (In.)	Wt. (Lbs.)	Model	Stock	PCN	Model	Stock	PCN	Model	Stock	PCN	
E1 General Purpose¹																
2	240	1	15	2	24-7/8	8	ARMTO-2020T3	NS	324208	ARMTO-2020T2	NS	324216	ARMTO-2020T1	NS	324224	
2	480	1	15	2	24-7/8	8	ARMTO-2020T3	NS	324267	ARMTO-2020T2	NS	324275	ARMTO-2020T1	NS	324283	
2.66	240	1	15	2	32-3/4	9	ARMTO-2026T3	NS	324320	ARMTO-2026T2	NS	324339	ARMTO-2026T1	NS	324347	
2.66	480	1	15	2	32-3/4	9	ARMTO-2026T3	NS	324380	ARMTO-2026T2	NS	324398	ARMTO-2026T1	NS	324400	
3.33	240	1	15	2	40-1/4	9	ARMTO-2033T3	NS	324443	ARMTO-2033T2	NS	324451	ARMTO-2033T1	NS	324460	
3.33	480	1	15	2	40-1/4	9	ARMTO-2033T3	NS	324507	ARMTO-2033T2	NS	324515	ARMTO-2033T1	NS	324523	
4	208	1	15	2	47-3/4	10	ARMTO-2040T3	NS	324566	ARMTO-2040T2	NS	324574	ARMTO-2040T1	NS	324582	
4	240	1	15	2	47-3/4	10	ARMTO-2040T3	NS	324620	ARMTO-2040T2	NS	324638	ARMTO-2040T1	NS	324646	
4	480	1	15	2	47-3/4	10	ARMTO-2040T3	NS	324689	ARMTO-2040T2	NS	324697	ARMTO-2040T1	NS	324700	
5	240	1	15	2	57-1/2	11	ARMTO-2050T3	NS	324742	ARMTO-2050T2	NS	324750	ARMTO-2050T1	NS	324769	
5	480	1	15	2	57-1/2	11	ARMTO-2050T3	NS	324806	ARMTO-2050T2	NS	324814	ARMTO-2050T1	NS	324822	
6	240	1	15	2	67-3/4	12	ARMTO-2060T3	NS	324865	ARMTO-2060T2	NS	324873	ARMTO-2060T1	NS	324881	
6	480	1	15	2	67-3/4	12	ARMTO-2060T3	NS	324929	ARMTO-2060T2	NS	324937	ARMTO-2060T1	NS	324945	
E2 Moisture Resistant/Explosion Resistant²																
2	240	1	15	2	24-7/8	13	ARMTO-2020E2T3	NS	324232	ARMTO-2020E2T2	NS	324240	ARMTO-2020E2T1	NS	324259	
2	480	1	15	2	24-7/8	13	ARMTO-2020E2T3	NS	324291	ARMTO-2020E2T2	NS	324304	ARMTO-2020E2T1	NS	324312	
2.66	240	1	15	2	32-3/4	14	ARMTO-2026E2T3	NS	324355	ARMTO-2026E2T2	NS	324363	ARMTO-2026E2T1	NS	324371	
2.66	480	1	15	2	32-3/4	14	ARMTO-2026E2T3	NS	324419	ARMTO-2026E2T2	NS	324427	ARMTO-2026E2T1	NS	324435	
3.33	240	1	15	2	40-1/4	14	ARMTO-2033E2T3	NS	324478	ARMTO-2033E2T2	NS	324486	ARMTO-2033E2T1	NS	324494	
3.33	480	1	15	2	40-1/4	14	ARMTO-2033E2T3	NS	324531	ARMTO-2033E2T2	NS	324540	ARMTO-2033E2T1	NS	324558	
4	208	1	15	2	47-3/4	15	ARMTO-2040E2T3	NS	324590	ARMTO-2040E2T2	NS	324603	ARMTO-2040E2T1	NS	324611	
4	240	1	15	2	47-3/4	15	ARMTO-2040E2T3	NS	324654	ARMTO-2040E2T2	NS	324662	ARMTO-2040E2T1	NS	324670	
4	480	1	15	2	47-3/4	15	ARMTO-2040E2T3	NS	324718	ARMTO-2040E2T2	NS	324726	ARMTO-2040E2T1	NS	324734	
5	240	1	15	2	57-1/2	16	ARMTO-2050E2T3	NS	324777	ARMTO-2050E2T2	NS	324785	ARMTO-2050E2T1	NS	324793	
5	480	1	15	2	57-1/2	16	ARMTO-2050E2T3	NS	324830	ARMTO-2050E2T2	NS	324849	ARMTO-2050E2T1	NS	324857	
6	240	1	15	2	67-3/4	17	ARMTO-2060E2T3	NS	324890	ARMTO-2060E2T2	NS	324902	ARMTO-2060E2T1	NS	324910	
6	480	1	15	2	67-3/4	17	ARMTO-2060E2T3	NS	324953	ARMTO-2060E2T2	NS	324961	ARMTO-2060E2T1	NS	324970	

Stock Status: S = stock NS = non-stock
To Order—Specify model, volts, phase, kW, PCN and quantity.

1. Heaters with General Purpose Enclosures are UL Listed with T1 or T2 Temperature and CSA Certified with T1, T2 or T3 Temperature.
2. Heaters with Moisture Resistant/Explosion Resistant Enclosures are _CCSA_{US}® Certified with T1, T2 or T3 Temperature.