


## ARMTS-3 Process Water Applications



- 2-1/2" NPT Stainless Steel Passivated Screw Plug
- Stainless Steel Passivated Sheath Elements
- High Watt Density (46 - 53 W/In<sup>2</sup>)
- 3 - 18 kW
- Integral Thermostat (DPST)
- 208, 240 and 480 Volt, Three Phase
- General Purpose Terminal Enclosure

*E1 — Dimensions (Inches)*



### Specifications and Ordering Information

							T2 — Temperature (60 - 250°F)			T1 — Temperature (0 - 100°F)		
kW	Volts	Phase	W/In <sup>2</sup>	Elem.	DIM B (In.)	Wt. (Lbs.)	Model	Stock	PCN	Model	Stock	PCN
<b>E1 General Purpose</b>												
3	208	3	51	3	7	8	ARMTS-3305T2	NS	187100	ARMTS-3305T1	NS	187119
3	240	3	51	3	7	8	ARMTS-3305T2	NS	184786	ARMTS-3305T1	NS	184823
3	480	3	51	3	7	8	ARMTS-3305T2	NS	184794	ARMTS-3305T1	NS	184831
4.5	208	3	48	3	11	8	ARMTS-3455T2	NS	187143	ARMTS-3455T1	NS	187151
4.5	240	3	48	3	11	8	ARMTS-3455T2	NS	184866	ARMTS-3455T1	NS	184903
4.5	480	3	48	3	11	8	ARMTS-3455T2	NS	184874	ARMTS-3455T1	NS	184911
6	208	3	48	3	17	9	ARMTS-3605T2	NS	187186	ARMTS-3605T1	NS	187194
6	240	3	48	3	17	9	ARMTS-3605T2	NS	184946	ARMTS-3605T1	NS	184989
6	480	3	48	3	17	9	ARMTS-3605T2	NS	184955	ARMTS-3605T1	NS	184997
7.5	208	3	53	3	18-1/2	10	ARMTS-3755T2	NS	187223	ARMTS-3755T1	NS	187231
7.5	240	3	53	3	18-1/2	10	ARMTS-3755T2	NS	185025	ARMTS-3755T1	NS	185068
7.5	480	3	53	3	18-1/2	10	ARMTS-3755T2	NS	185033	ARMTS-3755T1	NS	185076
9	208	3	47	3	24	10	ARMTS-3905T2	NS	187266	ARMTS-3905T1	NS	187274
9	240	3	47	3	24	10	ARMTS-3905T2	NS	185105	ARMTS-3905T1	NS	185148
9	480	3	47	3	24	10	ARMTS-3905T2	NS	185113	ARMTS-3905T1	NS	185156
12	208	3	46	3	32	11	ARMTS-3120T2	NS	187305	ARMTS-3120T1	NS	187311
12	240	3	46	3	32	11	ARMTS-3120T2	NS	185180	ARMTS-3120T1	NS	185228
12	480	3	46	3	32	11	ARMTS-3120T2	NS	185199	ARMTS-3120T1	NS	185236
15	208	3	46	3	39-1/2	12	ARMTS-3150T2	NS	187346	ARMTS-3150T1	NS	187354
15	240	3	46	3	39-1/2	12	ARMTS-3150T2	NS	185260	ARMTS-3150T1	NS	185308
15	480	3	46	3	39-1/2	12	ARMTS-3150T2	NS	185279	ARMTS-3150T1	NS	185316
18	208	3	51	3	47	13	ARMTS-3180T2 <sup>1</sup>	NS	187389	ARMTS-3180T1 <sup>1</sup>	NS	187397
18	240	3	51	3	47	13	ARMTS-3180T2	NS	185340	ARMTS-3180T1	NS	185383
18	480	3	51	3	47	13	ARMTS-3180T2	NS	185359	ARMTS-3180T1	NS	185391

**Stock Status:** S = stock NS = non-stock  
**To Order**—Specify model, volts, phase, kW, PCN and quantity.

1. Not UL Listed or CSA Certified (Exceeds 48 Amps).

**FASTShip**<sup>™</sup>

Same-day shipping on stock item orders received before 4 pm CST.  
 3-day shipping on assembly-stock items.

## ARMTS-3


### Process Water Applications (cont'd.)



SCREW PLUG

- 2-1/2" NPT Stainless Steel Passivated Screw Plug
- Stainless Steel Passivated Sheath Elements
- High Watt Density (46 - 53 W/In<sup>2</sup>)
- 3 - 18 kW
- Integral Thermostat (DPST)
- 208, 240 and 480 Volt, Single Phase
- Moisture Resistant/Explosion Resistant Terminal Enclosure

*E2 — Dimensions (Inches)*



### Specifications and Ordering Information

							T2 — Temperature (60 - 250°F)			T1 — Temperature (0 - 100°F)		
kW	Volts	Phase	W/In <sup>2</sup>	No. Elem.	DIM B (In.)	Wt. (Lbs.)	Model	Stock	PCN	Model	Stock	PCN
<b>E2 Moisture Resistant/Explosion Resistant</b>												
3	208	3	51	3	7	13	ARMTS-3305E2T2	NS	187127	ARMTS-3305E2T1	NS	187135
3	240	3	51	3	7	13	ARMTS-3305E2T2	NS	184807	ARMTS-3305E2T1	NS	184840
3	480	3	51	3	7	13	ARMTS-3305E2T2	NS	184815	ARMTS-3305E2T1	NS	184858
4.5	208	3	48	3	11	13	ARMTS-3455E2T2	NS	187160	ARMTS-3455E2T1	NS	187178
4.5	240	3	48	3	11	13	ARMTS-3455E2T2	NS	184882	ARMTS-3455E2T1	NS	184920
4.5	480	3	48	3	11	13	ARMTS-3455E2T2	NS	184890	ARMTS-3455E2T1	NS	184938
6	208	3	48	3	17	14	ARMTS-3605E2T2	NS	187207	ARMTS-3605E2T1	NS	187215
6	240	3	48	3	17	14	ARMTS-3605E2T2	NS	184962	ARMTS-3605E2T1	NS	185009
6	480	3	48	3	17	14	ARMTS-3605E2T2	NS	184970	ARMTS-3605E2T1	NS	185017
7.5	208	3	53	3	18-1/2	15	ARMTS-3755E2T2	NS	187240	ARMTS-3755E2T1	NS	187258
7.5	240	3	53	3	18-1/2	15	ARMTS-3755E2T2	NS	185041	ARMTS-3755E2T1	NS	185084
7.5	480	3	53	3	18-1/2	15	ARMTS-3755E2T2	NS	185050	ARMTS-3755E2T1	NS	185092
9	208	3	47	3	24	15	ARMTS-3905E2T2	NS	187282	ARMTS-3905E2T1	NS	187290
9	240	3	47	3	24	15	ARMTS-3905E2T2	NS	185121	ARMTS-3905E2T1	NS	185164
9	480	3	47	3	24	15	ARMTS-3905E2T2	NS	185130	ARMTS-3905E2T1	NS	185172
12	208	3	46	3	32	16	ARMTS-3120E2T2	NS	187320	ARMTS-3120E2T1	NS	187338
12	240	3	46	3	32	16	ARMTS-3120E2T2	NS	185201	ARMTS-3120E2T1	NS	185244
12	480	3	46	3	32	16	ARMTS-3120E2T2	NS	185210	ARMTS-3120E2T1	NS	185252
15	208	3	46	3	39-1/2	17	ARMTS-3150E2T2	NS	187362	ARMTS-3150E2T1	NS	187370
15	240	3	46	3	39-1/2	17	ARMTS-3150E2T2	NS	185287	ARMTS-3150E2T1	NS	185324
15	480	3	46	3	39-1/2	17	ARMTS-3150E2T2	NS	185295	ARMTS-3150E2T1	NS	185332
18	208	3	51	3	47	18	ARMTS-3180E2T2 <sup>1</sup>	NS	187400	ARMTS-3180E2T1 <sup>1</sup>	NS	187418
18	240	3	51	3	47	18	ARMTS-3180E2T2	NS	185367	ARMTS-3180E2T1	NS	185404
18	480	3	51	3	47	18	ARMTS-3180E2T2	NS	185375	ARMTS-3180E2T1	NS	185412

Stock Status: S = stock NS = non-stock  
To Order— Specify model, volts, phase, kW, PCN and quantity.

1. Not cCSA<sub>US</sub>® Certified (Exceeds 48 Amps).

**FASTShip**

Same-day shipping on stock item orders received before 4 pm CST. 3-day shipping on assembly-stock items.