

## FT-66 Fiberglass Tape PCN 512680

66' roll glass cloth installation tape with pressure sensitive thermosetting adhesive. 3/8" wide. 500°F (260°C) rating. Strap at one foot intervals. Minimum application temperature 40°F (5°C).

| Tape Type | Rolls Needed per 100' of Pipe |   |   |   |   |   |    |    |    |
|-----------|-------------------------------|---|---|---|---|---|----|----|----|
|           | Pipe Dia. (In.)               |   |   |   |   |   |    |    |    |
|           | 1/2"                          | 1 | 2 | 3 | 4 | 6 | 8  | 10 | 12 |
| FT-66     | 1                             | 2 | 4 | 4 | 6 | 8 | 10 | 12 | 15 |



## AT-18 Aluminum Tape Cable Attachments PCN 514204

180' roll aluminum foil installation tape with pressure sensitive acrylic adhesive. 2-mil thickness with high tensile strength; 2-1/2" wide. 200°F (93°C) rating. Minimum application temperatures 40°F (5°C).



## SS-1, SS-3, SS-10, SS-20 Stainless Steel Pipe Straps PCN 512070, 512719, 512727, 512735

Used for attaching DL and U Series kits to pipe.

|       |                                 |
|-------|---------------------------------|
| SS-1  | 1/2" to 3/4" pipes (PCN 512070) |
| SS-3  | 1" to 3-1/2" pipes (PCN 512719) |
| SS-10 | 2-1/2" to 9" pipes (PCN 512727) |
| SS-20 | 9" to 19.5" pipes (PCN 512735)  |



## WL-05 Caution Labels PCN 512743

(5) electric heat tracing caution labels, weather resistant.



## CH-75 Conduit Hub w/ Grounding Lug PCN 512751

Corrosion resistant hub for 3/4" conduit. Fits opening in PJB, DL, U Series and DTS. Includes ground connector.



# Commercial Self-Regulating & Constant Wattage Heat Trace Accessories

## MP-1 Mounting Plate Kit Attachments PCN 514239

For installing RTPC and RTST kits on flat surfaces.  
(For use with DL kits only)



## SSK Single Entry Sealing Kit\* PCN 514204

This kit provides water-resistant cable entry for one cable. It has a corrosion-resistant pipe stand-off that brings the cable end outside of the insulation for easy connection to power. A pipe strap (PS Series) is required to attach this model for a pipe. A small pipe adapter is available for pipe sizes less than 1-1/2". Customer supplied junction box required. (For use with EL kits only)

\*SSK to have these approvals when a junction box is used that is NEMA 4X rated and certified by appropriate third party agency for use for.



### Kit Includes:

- |                              |                                     |
|------------------------------|-------------------------------------|
| 1 Compression fitting        | 1 Self-regulating cable grommet     |
| 1 Locknut                    | 1 Constant wattage cable grommet    |
| 1 Silicone termination boots | 2 Uninsulated butt splice 14-16 AWG |
| 1 Pipe standoff              | 2 Insulated butt splice 14-16 AWG   |
| 1 O-ring                     |                                     |

## RG-PK-1 R&G Power Connection Kit PCN 513236

Power termination into junction box with one end seal and two warning labels.



## RG-SK-1 R&G Power Splice Kit PCN 513244

Materials to make one splice connection. Special weatherproof sleeving to insure trouble-free operation.



# Commercial Self-Regulating & Constant Wattage Heat Trace Accessories

## RG-EK-1 R&G End Seal Kit PCN 513252

Materials to make one end seal.



## RCK-1 R&G Roof Clips PCN 513260

Pack of ten (10) Roof clips to attached heating cable to surface.



## RDK-1 R&G Downspout Hanger Kit PCN 513279

Materials to suspend cable down a downspout.



## LA-03, LA-10, LA-50 Ambient Sensing Heat Trace RTD PCN 512768, 512778, 512786

- LA-03 3' Long 100 ohm Platinum RTD w/FEP Insulation and 2" Leads (PCN 512768)
- LA-10 10' Long 100 ohm Platinum RTD w/FEP Insulation and 2" Leads (PCN 512778)
- LA-50 50' Long 100 ohm Platinum RTD w/FEP Insulation and 2" Leads (PCN 512786)



## LN-03, LN-10, LN-50 Line Sensing Heat Trace RTD PCN 512794, 512807, 512815


- LN-03 3' Long 100 ohm Platinum RTD w/ FEP Insulation, flex armor, 1/2" fitting and 18" Leads (PCN 512794)
- LN-10 10' Long 100 ohm Platinum RTD w/ FEP Insulation, flex armor, 1/2" fitting and 18" Leads (PCN 512807)
- LN-50 50' Long 100 ohm Platinum RTD w/ FEP Insulation, flex armor, 1/2" fitting and 18" Leads (PCN 512815)



## Commercial Self-Regulating & Constant Wattage Heat Trace Accessories

### **AS-BM Ambient Sensing Heat Trace RTD PCN 512823**

Sensor is used for measuring the ambient air temperature. The 100 ohm Platinum RTD sensor element is made up with a Copper sheath and can be installed directly to a controller or junction box using the 1/2" NPT conduit fitting. The 304 SS guard protects the probe against accidental damage.



### **PS-AH Line Sensing Heat Trace RTD PCN 512831**

Sensor used for measuring the surface temperature of piping or vessels. The 100 ohm Platinum RTD sensor element is made up with a 316 SS sheath, and with a flexible stainless steel mounting pad.

