SL-N

Silicone Rubber Insulated General Purpose Heater

- Standard Pre-Designed Sizes and Ratings
- Most Models Stocked
- Square, Rectangular and Round Shapes
- Chemical and Moisture Resistant
- 10" Leads
- Flexible
- Standard 1" Square to 12" W x 48" L in 120 Volts
- Custom Designed Models Available



Description

Standard Chromalox Silicone Rubber heaters are pre-designed and available in a wide array of sizes and ratings to meet customer needs. Some models are stocked and can be shipped within 24 hours from receipt of your order. All standard models incorporate 10" silicone insulated stranded lead wire. Stocked items can be modified to include pressure sensitive adhesive but, will require additional lead time.

- Standard Thickness Ranges from 0.030" to 0.060" except at Lead Pad which is 0.15" Thick Depending on Design.
- Standard Resistance Tolerance is +10%, -5%.
- Silicon Rubber Material Temperature Range -80°F to +390°F

Specifications and Ordering Information

Watts	Volts	DIM (In.) Width	DIM (In.) Length	Model	Stock	PCN
25	120	1	5	SL-N-1-5-O-10-120V-25W	S	121515
50	120	1	10	SL-N-1-10-O-10-120V-50W	S	121523
100	120	1	20	SL-N-1-20-O-10-120V-100W	S	121540
150	120	1	30	SL-N-1-30-O-10-120V-150W	S	121566
200	120	1	40	SL-N-1-40-O-10-120V-200W	S	121582
400	120	1	80	SL-N-1-80-O-10-120V-400W	S	121590
20	120	2	2	SL-N-2-2-O-10-120V-20W	S	121611
50	120	2	5	SL-N-2-5-O-10-120V-50W	S	121620
100	120	2	10	SL-N-2-10-O-10-120V-100W	S	121638
150	120	2	15	SL-N-2-15-O-10-120V-150W	S	121646
200	120	2	20	SL-N-2-20-O-10-120V-200W	S	121654
200	240	2	20	SL-N-2-20-O-10-240V-200W	S	121662
75	120	3	5	SL-N-3-5-O-10-120V-75W	S	121726
150	120	3	10	SL-N-3-10-O-10-120V-150W	S	121734
225	120	3	15	SL-N-3-15-O-10-120V-225W	S	121742
300	120	3	20	SL-N-3-20-O-10-120V-300W	S	121769
300	240	3	20	SL-N-3-20-O-10-240V-300W	S	121777
375	120	3	25	SL-N-3-25-O-10-120V-375W	S	121785
600	120	3	40	SL-N-3-40-O-10-120V-600W	S	121814
200	120	4	10	SL-N-4-10-O-10-120V-200W	S	121822
250	120	5	10	SL-N-5-10-O-10-120V-250W	S	121849
375	120	5	15	SL-N-5-15-O-10-120V-375W	S	121857
500	120	5	20	SL-N-5-20-O-10-120V-500W	S	121865
450	120	6	15	SL-N-6-15-O-10-120V-450W	S	121873
600	120	6	20	SL-N-6-20-O-10-120V-600W	S	121881

Stock Status: **S** = stock NS = non-stock
To Order—Specify model, PCN and quantity.

Note — All supplied with standard 10" leads.