

TLC & KTLC

L-Shaped Metal Sheath Heaters

- Copper Sheath Elements (40 W/in²)
- 304 SS Riser
- 2 - 18 kW
- 120, 240 and 480V, 1 & 3 Phase
- Moisture Resistant Terminal Enclosure
- For Clean Water



Specifications and Ordering Information

kW	Volts	Phase	Riser A - DIM (In.)	Straight Elements				Circular Elements				Wt. (Lbs.)
				Min. Tank Clearance B - DIM (In.)	Model	Stock	PCN	Min. Tank Clearance B - DIM (In.)	Model	Stock	PCN	
2 Elements — Copper (40 W/In ²)												
2	120	1	36	12-1/4	TLC-220A-036	NS	193375	10-5/8	KTLC-220A-036	NS	183134	7
2	240	1	36	12-1/4	TLC-220A-036	NS	193383	10-5/8	KTLC-220A-036	NS	183142	7
2	480	1	36	12-1/4	TLC-220A-036	NS	193391	10-5/8	KTLC-220A-036	NS	183150	7
4	120	1	36	22-1/4	TLC-240A-036	NS	193404	13-3/4	KTLC-240A-036	NS	183169	9
4	240	1	36	22-1/4	TLC-240A-036	NS	193412	13-3/4	KTLC-240A-036	NS	183177	9
4	480	1	36	22-1/4	TLC-240A-036	NS	193420	13-3/4	KTLC-240A-036	NS	183185	9
6	120	1	36	29-1/2	TLC-260A-036 ¹	NS	193439	16-1/8	KTLC-260A-036 ¹	NS	183193	9
6	240	1	36	29-1/2	TLC-260A-036	NS	193447	16-1/8	KTLC-260A-036	NS	183206	9
6	480	1	36	29-1/2	TLC-260A-036	NS	193455	16-1/8	KTLC-260A-036	NS	183214	9
4.5/6	208/240	1	48	29-1/2	TLC-260TI-048	S	277755	—	—	—	—	11
8	240	1	36	37-3/8	TLC-280A-036	NS	193463	18-5/8	KTLC-280A-036	NS	183222	11
8	480	1	36	37-3/8	TLC-280A-036	NS	193471	18-5/8	KTLC-280A-036	NS	183230	11
10	240	1	48	45	TLC-210A-048	NS	193480	21-1/4	KTLC-210A-048	NS	183249	14
10	480	1	48	45	TLC-210A-048	NS	193498	21-1/4	KTLC-210A-048	NS	183257	14
12	240	1	48	52-1/2	TLC-212A-048 ¹	NS	193500	23-1/2	KTLC-212A-048 ¹	NS	183265	16
12	480	1	48	52-1/2	TLC-212A-048	NS	193519	23-1/2	KTLC-212A-048	NS	183273	16
3 Elements — Copper (40 W/In ²)												
3	120	1	36	12-1/4	TLC-330A-036	NS	194466	10-5/8	KTLC-330A-036	NS	183281	12
3	240	1	36	12-1/4	TLC-330A-036	NS	194482	10-5/8	KTLC-330A-036	NS	183290	12
3	240	3	36	12-1/4	TLC-330A-036	NS	277712	10-5/8	KTLC-330A-036	NS	183302	12
3	480	1	36	12-1/4	TLC-330A-036	NS	194503	10-5/8	KTLC-330A-036	NS	183310	12
3	480	3	36	12-1/4	TLC-330A-036	NS	194511	10-5/8	KTLC-330A-036	NS	183329	12
6	120	1	36	22-1/4	TLC-360A-036 ¹	NS	194520	13-3/4	KTLC-360A-036 ¹	NS	183337	12
6	240	1	36	22-1/4	TLC-360A-036	NS	194546	13-3/4	KTLC-360A-036	NS	183345	12
6	240	3	36	22-1/4	TLC-360A-036	NS	277720	13-3/4	KTLC-360A-036	NS	183353	12
6	480	1	36	22-1/4	TLC-360A-036	NS	194562	13-3/4	KTLC-360A-036	NS	183361	12
6	480	3	36	22-1/4	TLC-360A-036	NS	277739	13-3/4	KTLC-360A-036	NS	183370	12
9	120	1	36	29-1/2	TLC-390A-036 ¹	NS	194589	16-1/8	KTLC-390A-036 ¹	NS	183388	13
9	240	1	36	29-1/2	TLC-390A-036	NS	194600	16-1/8	KTLC-390A-036	NS	183396	13
9	240	3	36	29-1/2	TLC-390A-036	NS	194618	16-1/8	KTLC-390A-036	NS	183409	13
9	480	1	36	29-1/2	TLC-390A-036	NS	194626	16-1/8	KTLC-390A-036	NS	183417	13
9	480	3	36	29-1/2	TLC-390A-036	NS	194634	16-1/8	KTLC-390A-036	NS	183425	13
12	240	1	48	37-3/8	TLC-312A-048 ¹	NS	194642	18-5/8	KTLC-312A-048 ¹	NS	183433	16
12	240	3	48	37-3/8	TLC-312A-048	NS	194650	18-5/8	KTLC-312A-048	NS	183441	16
12	480	1	48	37-3/8	TLC-312A-048	NS	194669	18-5/8	KTLC-312A-048	NS	183450	16
12	480	3	48	37-3/8	TLC-312A-048	NS	277747	18-5/8	KTLC-312A-048	NS	183468	16
15	240	1	48	45	TLC-315A-048 ¹	NS	194685	21-1/4	KTLC-315A-048 ¹	NS	183476	17
15	240	3	48	45	TLC-315A-048	NS	194693	21-1/4	KTLC-315A-048	NS	183484	17
15	480	1	48	45	TLC-315A-048	NS	194706	21-1/4	KTLC-315A-048	NS	183492	17
15	480	3	48	45	TLC-315A-048	NS	194714	21-1/4	KTLC-315A-048	NS	183505	17
18	240	1	48	52-1/2	TLC-318A-048 ¹	NS	194722	23-1/2	KTLC-318A-048 ¹	NS	183513	18
18	240	3	48	52-1/2	TLC-318A-048	NS	194730	23-1/2	KTLC-318A-048	NS	183521	18
18	480	1	48	52-1/2	TLC-318A-048	NS	194749	23-1/2	KTLC-318A-048	NS	183530	18
18	480	3	48	52-1/2	TLC-318A-048	NS	194757	23-1/2	KTLC-318A-048	NS	183548	18

Stock Status: S = stock NS = non-stock
To Order—Specify model, PCN, kW, volts, phase and quantity.

Note — Thermostat Kit Option: 0 - 100°F (AR-115 Kit, PCN 277835); 60 - 250°F (AR-2529 Kit, PCN 277819)

1. Not UL or CSA (units exceed 48 Amps). Contact your Local Chromalox Sales office for additional circuits to comply with 48 Amp maximum.